



# レリコン® RELICON® Y分岐接続タイプ選定表

## 600V 単心 CV・VV ケーブル

分岐線 (mm <sup>2</sup> ) \ 本線 (mm <sup>2</sup> )	5.5	8	14	22	38	60	100	150	200
5.5									
8									
14									
22	Y-0/SF								
38	Y-0/SF								
60	Y-1/SF								
100	Y-1/SF								
150	Y-1/SF								
200	Y-3/SF								
250	Y-3/SF								
325	Y-3/SF								

## 波付鋼管がい装 CV ケーブル (コルゲートケーブル)

分岐線 (mm <sup>2</sup> ) \ 本線 (mm <sup>2</sup> )	2			3.5			5.5			8			14			22			
	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	
2	2C																		
	3C																		
	4C																		
3.5	2C																		
	3C																		
	4C	Y-1/SF																	
5.5	2C																		
	3C																		
	4C	Y-1/SF																	
8	2C																		
	3C																		
	4C																		
14	2C																		
	3C																		
	4C	Y-3/SF																	
22	2C																		
	3C																		
	4C																		
38	2C																		
	3C																		
	4C																		

## CV・VV ケーブル

分岐線 (mm <sup>2</sup> ) \ 本線 (mm <sup>2</sup> )	2			3.5			5.5			8			14			22			38			
	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	2C	3C	4C	
2	2C																					
	3C																					
	4C																					
3.5	2C																					
	3C																					
	4C	Y-0/SF																				
5.5	2C																					
	3C																					
	4C	Y-0/SF																				
8	2C																					
	3C																					
	4C	Y-1/SF																				
14	2C																					
	3C																					
	4C	Y-1/SF																				
22	2C																					
	3C																					
	4C	Y-3/SF																				
38	2C																					
	3C																					
	4C	Y-3/SF																				

※ Y分岐接続の導体接続はC型またはT型コネクタをご使用ください。